

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
12 May 2005 (12.05.2005)

PCT

(10) International Publication Number
WO 2005/043653 A1

(51) International Patent Classification⁷: **H01M 4/58**,
4/02, 10/40

Denko K.K., 6850 Oaza Omachi, Omachi-Shi, Nagano
398-0002 (JP).

(21) International Application Number:
PCT/JP2004/016482

(74) Agent: **OHIE, Kunihisa**; Ohie Patent Office,
Selva-Ningyocho 6F, 14-6, Nihonbashi-Ningyocho
2-chome, Chuo-ku, Tokyo 103-0013 (JP).

(22) International Filing Date: 29 October 2004 (29.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-371494 31 October 2003 (31.10.2003) JP
60/518,660 12 November 2003 (12.11.2003) US

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (*for all designated States except US*): **SHOWA DENKO K.K.** [JP/JP]; 13-9, Shiba Daimon 1-chome, Minato-ku, Tokyo 105-8518 (JP).

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **SOTOWA, Chiaki** [JP/JP]; c/o Corporate R & D Center, Showa Denko K.K., 5-1, Okawacho, Kawasaki-ku, Kawasaki-shi, Kanagawa 210-0858 (JP). **TAKEUCHI, Masataka** [JP/JP]; c/o Corporate R & D Center, Showa Denko K.K., 5-1 Okawacho, Kawasaki-ku, Kawasaki-shi, Kanagawa 210-0858 (JP). **SUDOH, Akinori** [JP/JP]; c/o Omachi Plant, Showa

Published:
— with international search report

[Continued on next page]

(54) Title: CARBON MATERIAL FOR BATTERY ELECTRODE AND PRODUCTION METHOD AND USE THEREOF



(57) Abstract: The invention provides a carbon material for a battery electrode, which comprises a carbon powder material as a composite of carbonaceous particles and an a carbon material derived from an organic compound prepared by allowing the organic compound serving as a polymer source material to deposit onto and/or permeate into the carbonaceous particles to thereby polymerize the polymer material and then heating at 1,800 to 3,300°C, and which has an intensity ratio of 0.1 or more for peak intensity attributed to a (110) plane to peak intensity attributed to a (004) plane determined through X-ray diffraction spectroscopic analysis on a mixture of the carbon material and a binder resin when pressed at 10³ kg/cm² or higher. The carbon material which undergoes less deformation/orientation due to application of pressure, has high discharge capacity and small irreversible capacity and exhibiting excellent coulombic efficiency, cycle characteristics and leakage-current load characteristics.

WO 2005/043653 A1

WO 2005/043653 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.